



- ① Concrete Deck primed with Fix-R quick dry primer
- ② SIG D&T SIGnature Torch On Vapour Control Layer
- ③ IKO Enertherm ALU Insulation or Recticel Liquid Board - bonded with IKOPro high performance PU adhesive. Board Joints to be sealed with Hydrostop AH-25 jointing tape.
- ④ Hydrostop AH-25 Jointing Tape
- ⑤ Base Coat AH-25
- ⑥ AH25 Reinforcing Fabric
- ⑦ Top Coat AH-25

Waterproofing should be installed in accordance with BS 6229:2003.

AH-25 Primer Chart should be consulted for relevant Primer/Blocker to be utilised before commencing with AH-25 waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH-25 products and services can be obtained through the contact details printed below.



SIG Design & Technology
 Mannheim House, Gelders Hall Road
 Shepshed, Leicestershire LE12 9NH
 Tel: 0844 443 4778 Fax: 01509 505475
 Internet: www.singleply.co.uk
 Email: info@singleply.co.uk

TITLE:

AH-25 WARM ROOF BUILD-UP

DATE:

10.01.2017

DRAWN BY:

RH

SCALE:

NTS

DRAWING No:

AH25-0C

REVISION: