



- ① Concrete Deck primed with Fix-R quick dry primer
- ② SIG D&T SIGNature Torch On Vapour Control Layer
- ③ IKO Enertherm ALU Insulation or Recticel Liquid Board - bonded with IKOPro high performance PU adhesive. Board Joints to be sealed with AH-25 jointing tape. Base Coat
- ④ AH-25
- ⑤ AH25 Reinforcing Fabric
- ⑥ Top Coat AH-25
- ⑦ 100mm overlap of upstand Liquid & Reinforcement to Field area Liquid & Reinforcement
- ⑧ AH-25 Jointing Tape
- ⑨ Min 18mm min Class 3 Plywood or OSB3 Upstand lining
- ⑩ Anti-Corrosive fixings
- ⑪ SIG D&T GRP Liquid Trim
- ⑫ 250mm AH25 Liquid & Reinforcing Membrane
- ⑬ Timber Facia / Wall Batten with Continuous Adhesive Bead
- ⑭ Brickwork by others

Waterproofing should be installed in accordance with BS 6229:2003.

AH-25 Primer Chart should be consulted for relevant Primer/Blocker to be utilised before commencing with AH-25 waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH-25 products and services can be obtained through the contact details printed below.



SIG Design & Technology
 Mannheim House, Gelders Hall Road
 Shepshed, Leicestershire LE12 9NH
 Tel: 0844 443 4778 Fax: 01509 505475
 Internet: www.singleply.co.uk
 Email: info@singleply.co.uk

TITLE:
**AH-25 PARAPET DETAIL
 UNINSULATED**

DATE: 17.01.2017	DRAWN BY: RH	SCALE: NTS
---------------------	-----------------	---------------

DRAWING No: AH25-13C	REVISION:
-------------------------	-----------