



- ① Min 18mm Class 3 Plywood or OSB3 Deck primed with IKO Systems Bonding Agent
  - ② SIG D&T SIGNature Self Adhesive Vapour Control Layer
  - ③ IKO Enertherm ALU Insulation or Recticel Liquid Board - mech fixed. Board Joints to be sealed with AH-25 jointing tape.
  - ④ Base Coat AH-25
  - ⑤ AH25 Reinforcing Fabric
  - ⑥ Top Coat AH-25
  - ⑦ AH-25 Jointing Tape
  - ⑧ IKOfix Fastener & GOK-75 Thermally Broken Fixing Tube
  - ⑨ 100mm overlap of upstand Liquid & Reinforcement to Field area Liquid & Reinforcement
  - ⑩ Min 18mm min WBP Plywood or OSB3 Upstand lining
  - ⑪ Anti-Corrosive fixings
  - ⑫ SIG D&T GRP Liquid Trim
  - ⑬ 250mm AH25 Liquid & Reinforcing Membrane
  - ⑭ Timber Facia / Wall Batten with Continuous Adhesive Bead
  - ⑮ Brickwork by others
- Waterproofing should be installed in accordance with BS 6229:2003.

AH-25 Primer Chart should be consulted for relevant Primer/Blocker to be utilised before commencing with AH-25 waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH-25 products and services can be obtained through the contact details printed below.



SIG Design & Technology  
 Mannheim House, Gelders Hall Road  
 Shepshed, Leicestershire LE12 9NH  
 Tel: 0844 443 4778 Fax: 01509 505475  
 Internet: www.singleply.co.uk  
 Email: info@singleply.co.uk

TITLE:  
**AH-25 PARAPET DETAIL  
 UNINSULATED**

DATE: 17.01.2017	DRAWN BY: RH	SCALE: NTS
---------------------	-----------------	---------------

DRAWING No: AH25-13T	REVISION:
-------------------------	-----------