



- ① Metal Deck primed with appropriate primer to top of crowns
- ② SIG D&T SIGnature Self Adhesive or Torch On Vapour Control Layer
- ③ IKO Enertherm ALU Insulation or Recticel Liquid Board - mech fixed. Board Joints to be sealed with Hydrostop AH-25 Jointing Tape
- ④ Hydrostop AH-25 Jointing Tape
- ⑤ Base Coat AH-25
- ⑥ AH25 Reinforcing Fabric
- ⑦ Top Coat AH-25
- ⑧ Spectratex 300gr/m<sup>2</sup> fleece protection layer
- ⑨ Minimum 50mm thick Paving slabs on proprietary supports
- ⑩ Minimum 50mm layer of 20-40 rounded washed aggregate
- ⑪ Big foot frame by others

Waterproofing should be installed in accordance with BS 6229:2003.

AH-25 Primer Chart should be consulted for relevant Primer/Blocker to be utilised before commencing with AH-25 waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH-25 products and services can be obtained through the contact details printed below.



SIG Design & Technology  
 Mannheim House, Gelders Hall Road  
 Shepshed, Leicestershire LE12 9NH  
 Tel: 0844 443 4778 Fax: 01509 505475  
 Internet: [www.singleply.co.uk](http://www.singleply.co.uk)  
 Email: [info@singleply.co.uk](mailto:info@singleply.co.uk)

TITLE:

### AH-25 BIG FOOT DETAIL METAL DECK

DATE:

17.01.2017

DRAWN BY:

RH

SCALE:

NTS

DRAWING No:

AH25-15M

REVISION: