



- ① Metal Deck primed with appropriate primer to top of crowns
- ② SIG D&T SIGnature Self Adhesive or Torch On Vapour Control Layer
- ③ IKO Enertherm ALU Insulation or Recticel Liquid Board - mech fixed. Board Joints to be sealed with AH-25 Jointing Tape
- ④ AH-25 Jointing Tape
- ⑤ Base Coat AH-25
- ⑥ AH25 Reinforcing Fabric
- ⑦ Top Coat AH-25
- ⑧ Spectratex 300gr/m² fleece protection layer
- ⑨ Minimum 50mm thick Paving slabs on proprietary supports
- ⑩ Minimum 50mm layer of 20-40 rounded washed aggregate
- ⑪ Big foot frame by others

Waterproofing should be installed in accordance with BS 6229:2003.

AH-25 Primer Chart should be consulted for relevant Primer/Blocker to be utilised before commencing with AH-25 waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH-25 products and services can be obtained through the contact details printed below.



SIG Design & Technology
 Mannheim House, Gelders Hall Road
 Shepshed, Leicestershire LE12 9NH
 Tel: 0844 443 4778 Fax: 01509 505475
 Internet: www.singleply.co.uk
 Email: info@singleply.co.uk

TITLE:
**AH-25 BIG FOOT DETAIL
 METAL DECK**

DATE: 17.01.2017	DRAWN BY: RH	SCALE: NTS
---------------------	-----------------	---------------

DRAWING No: AH25-15M	REVISION:
-------------------------	-----------