



- ① Concrete Deck primed with Fix-R quick dry primer
- ② SIG D&T SIGNature Torch On Vapour Control Layer
- ③ IKO Enertherm ALU Insulation or Recticel Liquid Board - bonded with IKOPro high performance PU adhesive. Board Joints to be sealed with AH-25 jointing tape. Base Coat
- ④ AH-25
- ⑤ AH-25 Reinforcing Fabric
- ⑥ Top Coat AH-25
- ⑦ 100mm overlap of upstand Liquid & Reinforcement to Field area Liquid & Reinforcement
- ⑧ Timber Hard Edge - mech fixed
- ⑨ Chased Lead flashing with Leadseal sealant
- ⑩ 20mm Liquid only to waterproofing termination
- ⑪ Brickwork by others
- ⑫ AH-25 Jointing Tape

Waterproofing should be installed in accordance with BS 6229:2003.

AH-25 Primer Chart should be consulted for relevant Primer/Blocker to be utilised before commencing with AH-25 waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH-25 products and services can be obtained through the contact details printed below.



SIG Design & Technology  
 Mannheim House, Gelders Hall Road  
 Shepshed, Leicestershire LE12 9NH  
 Tel: 0844 443 4778 Fax: 01509 505475  
 Internet: www.singleply.co.uk  
 Email: info@singleply.co.uk

TITLE:  
**AH-25 ABUTMENT TO INSULATED BRICK WALL - CONCRETE DECK**

DATE: 17.01.2017	DRAWN BY: RH	SCALE: NTS
---------------------	-----------------	---------------

DRAWING No: AH25-21C	REVISION:
-------------------------	-----------