



- ① Concrete Deck primed with Fix-R quick dry primer
- ② SIG D&T SIGNature Torch On Vapour Control Layer
- ③ IKO Enertherm ALU Insulation or Recticel Liquid Board - bonded with IKOPro high performance PU adhesive. Board Joints to be sealed with Hydrostop AH-25 jointing tape.
- ④ Base Coat AH-25
- ⑤ AH25 Reinforcing Fabric
- ⑥ Top Coat AH-25
- ⑦ Anti-Corrosive fixings
- ⑧ 500mm AH25 Liquid & Reinforcement
- ⑨ Galvanised Metal Hard Edge to be cleaned or Primed as appropriate
- ⑩ 100mm overlap of upstand Liquid & Reinforcement to Field area Liquid & Reinforcement
- ⑪ Hydrostop AH-25 Jointing Tape

Waterproofing should be installed in accordance with BS 6229:2003.

AH-25 Primer Chart should be consulted for relevant Primer/Blocker to be utilised before commencing with AH-25 waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH-25 products and services can be obtained through the contact details printed below.



SIG Design & Technology  
 Mannheim House, Gelders Hall Road  
 Shepshed, Leicestershire LE12 9NH  
 Tel: 0844 443 4778 Fax: 01509 505475  
 Internet: www.singleply.co.uk  
 Email: info@singleply.co.uk

TITLE:

### AH-25 BOX GUTTER/ CHANGE OF LEVEL DETAIL

DATE:

10.01.2017

DRAWN BY:

RH

SCALE:

NTS

DRAWING No:

AH25-3C

REVISION: