



- ① Metal Deck primed with appropriate primer to top of crowns
- ② SIG D&T SIGNature Self Adhesive or Torch On Vapour Control Layer
- ③ IKO Enertherm ALU Insulation or Recticel Liquid Board - mech fixed. Board Joints to be sealed with Hydrostop AH-25 Jointing Tape
- ④ Base Coat AH-25
- ⑤ AH25 Reinforcing Fabric
- ⑥ Top Coat AH-25
- ⑦ Hydrostop AH-25 Jointing Tape
- ⑧ IKOfix Fastener & GOK-75 Thermally Broken Fixing Tube
- ⑨ Anti-Corrosive fixings
- ⑩ 500mm AH25 Liquid & Reinforcement
- ⑪ Galvanised Metal Hard Edge
- ⑫ 100mm overlap of upstand Liquid & Reinforcement to Field area Liquid & Reinforcement

Waterproofing should be installed in accordance with BS 6229:2003.

AH-25 Primer Chart should be consulted for relevant Primer/Blocker to be utilised before commencing with AH-25 waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH-25 products and services can be obtained through the contact details printed below.



SIG Design & Technology
 Mannheim House, Gelders Hall Road
 Shepshed, Leicestershire LE12 9NH
 Tel: 0844 443 4778 Fax: 01509 505475
 Internet: www.singleply.co.uk
 Email: info@singleply.co.uk

TITLE:
**AH-25 BOX GUTTER/
 CHANGE OF LEVEL DETAIL
 METAL DECK**

| | | |
|---------------------|-----------------|---------------|
| DATE: 17.01.2017 | DRAWN BY: RH | SCALE: NTS |
|---------------------|-----------------|---------------|

| | |
|------------------------|-----------|
| DRAWING No: AH25-3M | REVISION: |
|------------------------|-----------|