



- ① Min 18mm Class 3 Plywood or OSB3 Deck primed with IKO Systems Bonding Agent
- ② SIG D&T SIGnature Self Adhesive Vapour Control Layer
- ③ IKO Enertherm ALU Insulation or Recticel Liquid Board - mech fixed. Board Joints to be sealed with Hydrostop AH-25 jointing tape.
- ④ Base Coat AH-25
- ⑤ Reinforcing Membrane
- ⑥ IKOfix Fastener & GOK-75 Thermally Broken Fixing Tube
- ⑦ Top Coat AH-25
- ⑧ Hydrostop AH-25 Jointing Tape
- ⑨ 500mm AH25 Liquid & Reinforcement
- ⑩ Anti-Corrosive fixings
- ⑪ SIG D&T Rainwater Outlet
- ⑫ Sealant by others

Waterproofing should be installed in accordance with BS 6229:2003.

AH-25 Primer Chart should be consulted for relevant Primer/Blocker to be utilised before commencing with AH-25 waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH-25 products and services can be obtained through the contact details printed below.



SIG Design & Technology
 Mannheim House, Gelders Hall Road
 Shepshed, Leicestershire LE12 9NH
 Tel: 0844 443 4778 Fax: 01509 505475
 Internet: www.singleply.co.uk
 Email: info@singleply.co.uk

TITLE:
AH-25 ROOF DRAIN DETAIL

DATE: 17.01.2017	DRAWN BY: RH	SCALE: NTS
---------------------	-----------------	---------------

DRAWING No: AH25-4T	REVISION:
------------------------	-----------