

# Spectraplan Accessories

Product Data Sheet  
June 2009

## A Range of Accessories to Complement Spectraplan TPE Membranes

### Preformed Outlets and Corners

Spectraplan Preformed Outlets and Corners are a range of preformed units manufactured from homogeneous TPE to enhance the installation of Spectraplan TPE Membranes.

Corner units are available in both internal and external configurations and are flexible and easy to mould and heat weld over the Spectraplan TPE Membrane to detail and waterproof corner areas.

Preformed Outlets are a range of preformed straight and 90° roof drain outlets available in a range of diameters. The outlet units are mechanically fixed into position and waterproofed with a cover flashing of Spectraplan TPE Membrane which is heat welded onto the outlet flange.

#### Product Details

##### Dimensions and Weights

	Internal Diameter	External Diameter	Base Plate Dimensions	Spigot Length
TPE Roof Drain, no angle	56 mm	60 mm	300 mm diameter	315 mm
TPE Roof Drain, no angle	63 mm	67 mm	300 mm diameter	315 mm
TPE Roof Drain, no angle	75 mm	79 mm	300 mm diameter	315 mm
TPE Roof Drain, no angle	90 mm	94 mm	300 mm diameter	315 mm
TPE Roof Drain, no angle	95 mm	99 mm	300 mm diameter	315 mm
TPE Roof Drain, no angle	110 mm	114 mm	300 mm diameter	315 mm
TPE Roof Drain, no angle	125 mm	129 mm	300 mm diameter	315 mm
TPE Roof Drain, no angle	140 mm	144 mm	300 mm diameter	315 mm
TPE Roof Drain, 90° angle	63 mm	67 mm	300 mm x 100 mm x 230 mm	450 mm
TPE Roof Drain, 90° angle	75 mm	79 mm	300 mm x 100 mm x 230 mm	450 mm
TPE Roof Drain, 90° angle	90 mm	94 mm	330 mm x 100 mm x 230 mm	450 mm

### Spectraclad Coated Metal

Spectraclad coated metal is a steel sheet pre-coated with homogeneous TPE membrane. The coated metal can be fabricated off-site to form perimeter details such as drip edges and upstands. The TPE membrane surfacing to the metal enables Spectraplan TPE Membranes to be heat welded to preformed edge details to ensure the perimeters are fully sealed and waterproofed.

#### Product Details

##### Dimensions and Weights

	Thickness	Sheet Width	Sheet Length
Spectraclad Precoated Metal Light Grey (RAL 7035)	1.6 mm	1 m	2 m
Spectraclad Precoated Metal Dark Grey (RAL 7011)			

### Spectraplan Standing Seam Profile

Spectraplan Standing Seam Profile is a preformed profile used to simulate a metal standing seam joint. The profile is manufactured from homogeneous TPE and is heat welded.

#### Product Details

##### Dimensions and Weights

	Length
Spectraplan Standing Seam Profile Light Grey (RAL 7035)	2 m
Spectraplan Standing Seam Profile Dark Grey (RAL 7011)	

## **Spectraclip**

Spectraclip Lightning Conductor Clips are polyethylene clips which can be directly heat welded to Spectraplan TPE Membranes to enable lightning conductor systems to be secured to the roof area. The clips should not be installed over any joints in the membrane and should be fitted at maximum of 1.0 m centres.

### **Product Details**

#### **Dimensions and Weights**

	Conductor Size
Spectraclip Grey	25 mm x 3 mm

### **Other Product Information**

Full product literature is available to download from our website: [www.singleply.co.uk](http://www.singleply.co.uk). Amourplan is only available from SIG Design & Technology and can only be installed by an IKO Single Ply trained and licensed contractors.



Follow on Twitter



Visit us on LinkedIn



Visit our Technical Blog

SIG Design & Technology  
Mannheim House  
Gelders Hall Road  
Shepshed  
Leicestershire LE12 9NH

[www.singleply.co.uk](http://www.singleply.co.uk)  
Tel: 01509 505714  
Fax: 01509 505475

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.

