

according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 4 Revision: 01.10.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier

**Hydrostop AH+ Concrete Primer Summer (A)** - Trade name:

- 1.2 Relevant identified uses of the substance or mixture and uses advised

Identified use: intended for professional use only!

- Application of the substance / the mixture - 1.3 Details of the supplier of the safety data sheet

SIG Trading Ltd, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH, - Manufacturer/Supplier:

United Kingdom

- Further information obtainable from: Representative for Hazardous Substances

01509 505 714 - 1.4 Emergency telephone number:

### **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. Skin Sens. 1 Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

- Hazard pictograms

The product is classified and labelled according to the CLP regulation.



- Signal word Warning

- Hazard-determining components of

labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Bisphenol F epichlorohydrin resin MW <700 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

- Hazard statements H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction.

- 2.3 Other hazards

- Results of PBT and vPvB assessment

Not applicable. - vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

3.2 Chemical characterisation: Mixtures

- Description: Mixture: consisting of the following components.

- Dangerous components:

CAS: 25068-38-6 NLP: 500-033-5

Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317

(Contd. on page 2)





### according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 4 Revision: 01.10.2019

Trade name: Hydrostop AH+ Concrete Primer Summer (A)

	(Conto	l. of page 1)
CAS: 9003-36-5	Bisphenol F epichlorohydrin resin MW <700	25-50%
NLP: 500-006-8	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	
Reg.nr.: 01-2119454392-40		
CAS: 68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	12.5-25%
EINECS: 271-846-8	Skin Irrit. 2, H315; Skin Sens. 1, H317	
Index number: 603-103-00-4		
Reg.nr.: 01-2119485289-22		
- Additional information:	For the wording of the listed hazard phrases refer to section 16.	

#### **SECTION 4: First aid measures**

- 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48

hours after the accident.

Do not leave affected persons unattended. Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints. - After skin contact: Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eye.

- After swallowing:

- 4.2 Most important symptoms and effects,

both acute and delayed

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

If symptoms persist consult doctor.

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the

substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters

- Protective equipment:

Do not inhale explosion gases or combustion gases.

- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective

equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin and eyes

- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers). Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment

and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

- 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

(Contd. on page 3)

(Contd. of page 2)



# Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 4 Revision: 01.10.2019

Trade name: Hydrostop AH+ Concrete Primer Summer (A)

- Information about fire - and explosion

**protection:** No special measures required.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and

receptacles:

Store only in the original receptacle.

- Information about storage in one common

storage facility:

Store away from foodstuffs.

- Further information about storage

conditions:

Protect from frost. Store in dry conditions.

Recommended storage temperature: 5-30 °C

Keep container tightly sealed.

- Storage class: 10

- 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- Additional information about design of

technical facilities: No further data; see item 7.

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

- DNELs

#### 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

Inhalative Acute - systemic effects 3.6 mg/m³ (Worker) (GESTIS DNEL List (June 2018))

Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Respiratory protection: When used properly and under normal conditions, breathing protection is not required.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Respiratory protection - Gas filters and combination filters according to (DIN EN 141)

- Protection of hands:



Protective gloves

Check protective gloves prior to each use for their proper condition. Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the

preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion

and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical

conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is

recommended.

- As protection from splashes gloves made of

the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.1 mm

Penetration time (min.): < 10

- Eye protection:



Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 4 Revision: 01.10.2019

Trade name: Hydrostop AH+ Concrete Primer Summer (A)

- Body protection: Protective work clothing

protective clothing (EN 13034)

(Contd. of page 3)

### **SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Fluid

Colour: According to product specification

Odour: Aromatic
 Odour threshold: Not determined.
 pH-value: Not determined.

- Change in condition

Melting point/freezing point:
Initial boiling point and boiling range:

- Flash point:

>200 °C

>100 °C

- Flammability (solid, gas): Not applicable.

- Ignition temperature: 300 °C

- **Decomposition temperature:** Not determined.

- Auto-ignition temperature: Product is not selfigniting.

- Explosive properties: Product does not present an explosion hazard

- Explosion limits: Lower:

Upper: Not determined.

- Density at 20 °C: 1.13 g/cm³

- Relative density Not determined.

- Vapour density Not determined.

- Evaporation rate Not determined.

- Solubility in / Miscibility with

water: Not miscible or difficult to mix.

- Partition coefficient: n-octanol/water: Not determined.

- Viscosity:

Dynamic at 20 °C: 900 mPas
Kinematic: Not determined.

- Solvent content:

**VOC (EC)** 1.08 %

- 9.2 Other information No further relevant information available

### **SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.

- 10.2 Chemical stability

- Thermal decomposition / conditions to be

avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.

- 10.4 Conditions to avoid
 - 10.5 Incompatible materials:
 - 10.6 Hazardous decomposition products:
 - 10.6 Hazardous decomposition products:

No further relevant information available.
No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- 11.1 Information on toxicological effects

- Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 4 Revision: 01.10.2019

Trade name: Hydrostop AH+ Concrete Primer Summer (A)

(Contd. of page 4) - LD/LC50 values relevant for classification: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < 700) LD50 11,400 mg/kg (rat) Dermal LD50 >2,000 mg/kg (rabbit) Inhalative LCLo 1 mg/l (rat) 9003-36-5 Bisphenol F epichlorohydrin resin MW <700 Oral LD50 23,800 mg/kg (rat) LD50 >2,000 mg/kg (rabbit) Dermal 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs LD50 19,200 mg/kg (rat) Oral LD50 >4,500 mg/kg (rabbit) Dermal

- Primary irritant effect:

- Skin corrosion/irritation
 - Serious eye damage/irritation
 - Respiratory or skin sensitisation
 - CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- Cerm cell mutagenicity
- Germ cell mutagenicity
- Carcinogenicity
- Reproductive toxicity
- Reproductive toxicity
- STOT-single exposure
- STOT-repeated exposure
- Aspiration hazard
- Carcinogenicity
- Based on available data, the classification criteria are not met.
- Based on available data, the classification criteria are not met.
- Based on available data, the classification criteria are not met.
- Based on available data, the classification criteria are not met.
- Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- 12.1 Toxicity

- Aqualic to	- Aquatic toxicity.			
25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)				
IC50	>42.6 mg/l (Bakterien) (18h)			
LC50/96 h	LC50/96 h 1.5 mg/l (fish) (OECD 203 (96 hr))			
	1.5 mg/l (Oncorhynchus mykiss (Regenbogenforelle))			
EC50 (24)	3.6 mg/l (dpa)			
EC50	1.8 mg/l (Daphnia magna) (48h)			
EC50	9.4 mg/l (ALGAE) (EPA CFR (72 hr))			
	1.7 mg/l (daphnia) (OECD 202 (48 hr))			
	11 mg/l (Selenastrum capricornutum) (72h)			
NOEC	0.3 mg/l (Daphnia magna) (21d)			
MATC	0.55 mg/l (Daphnia magna) (21d)			
9003-36-5 Bisphenol F epichlorohydrin resin MW <700				
LC50/96 h   >100 mg/l (fish)				
68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs				
EbC50	843 mg/l (Pseudokirchneriella subcapitata)			
LC50/96 h	1,800 mg/l (LEPOMUS MACROCHIRUS)			
	>5,000 mg/l (Oncorhynchus mykiss (Regenbogenforelle))			
NOEC	500 mg/l (Pseudokirchneriella subcapitata) (NOEC (72 hr))			
- 12.2 Persistence and degradability  No further relevant information available.				
- 12.3 Bioaccumulative potential No further relevant information available				

12.2 Persistence and degradability
 12.3 Bioaccumulative potential
 12.4 Mobility in soil
 No further relevant information available.
 No further relevant information available.

- Ecotoxical effects: - Remark:

Toxic for fish

- Additional ecological information:

- General notes: Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Revision: 01.10.2019 Version number 4

Trade name: Hydrostop AH+ Concrete Primer Summer (A)

No further relevant information available.

(Contd. of page 5)

### **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods

- 12.6 Other adverse effects

- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal according to official regulations

- European waste catalogue

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

- 14.7 Transport in bulk according to Annex II of Marpol and the IBC

Code

08 02 99 wastes not otherwise specified

- Uncleaned packaging:

- Recommendation:	Disposal must be made according to official regulations.	
SECTION 14: Transport inform	ation	
- 14.1 UN-Number - ADR, IMDG, IATA	UN3082	
- 14.2 UN proper shipping name - ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
- IMDG - IATA	(reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), Bisphenol F epichlorohydrin resin MW <700) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), Bisphenol F epichlorohydrin resin MW <700), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), Bisphenol F epichlorohydrin resin MW <700)	
<ul><li>- 14.3 Transport hazard class(es)</li><li>- ADR</li></ul>		
- Class - Label	9 (M6) Miscellaneous dangerous substances and articles. 9	
- IMDG, IATA		
- Class - Label	9 Miscellaneous dangerous substances and articles. 9	
- 14.4 Packing group		

- ADR, IMDG, IATA Ш - 14.5 Environmental hazards: Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ - Marine pollutant: Symbol (fish and tree) - Special marking (ADR): Symbol (fish and tree) - Special marking (IATA): Symbol (fish and tree) - 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. - Danger code (Kemler): 90 F-A,S-F - EMS Number: - Stowage Category

> Not applicable. (Contd. on page 7)





according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 4 Revision: 01.10.2019

Trade name: Hydrostop AH+ Concrete Primer Summer (A)

(Contd. of page 6) - Transport/Additional information: - Limited quantities (LQ) - Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml - Transport category - Tunnel restriction code - Limited quantities (LQ) - Excepted quantities (EQ) Code: F1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml - UN "Model Regulation": UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN

### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E2 Hazardous to the Aquatic Environment - Qualifying quantity (tonnes) for the

application of lower-tier requirements - Qualifying quantity (tonnes) for the

application of upper-tier requirements 500 t

**REGULATION (EC) No 1907/2006 ANNEX** 

- National regulations:

- Information about limitation of use: Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

Conditions of restriction: 3

Employment restrictions concerning women of child-bearing age must be observed.

NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700), BISPHÉNOL F

EPICHLOROHYDRIN RESIN MW <700), 9, III

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H315 Causes skin irritation.

> H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) - Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

- Sources Internet:

· www.echa.europa.eu

www.baua.de

IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:

www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp

- www.dguv.de/ifa/gestis/gestis-dnel-liste

(Contd. on page 8)





# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.10.2019 Version number 4 Revision: 01.10.2019

Trade name: Hydrostop AH+ Concrete Primer Summer (A)

- \* Data compared to the previous version altered.

(Contd. of page 7)