

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019

Version number 6


Revision: 01.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking


- 1.1 Product identifier **Hydrostop AH+ Concrete Primer Winter (A)**
- Trade name: **Hydrostop AH+ Concrete Primer Winter (A)**
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified use: intended for professional use only!
- Application of the substance / the mixture Primer
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: SIG Trading Ltd, Adsetts House, 16 Europa View, Sheffield Business Park, Sheffield, S9 1XH, United Kingdom
- Further information obtainable from: Representative for Hazardous Substances
- 1.4 Emergency telephone number: 01509 505 714

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008
 - Skin Irrit. 2 H315 Causes skin irritation.
 - Eye Irrit. 2 H319 Causes serious eye irritation.
 - Skin Sens. 1 H317 May cause an allergic skin reaction.
 - Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS07



GHS09
- Signal word Warning
- Hazard-determining components of labelling: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
Bisphenol F epichlorohydrin resin MW <700
oxirane, mono[(C12-14-alkyloxy)methyl] derivs
- Hazard statements H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P273 Avoid release to the environment.
 - P280 Wear protective gloves / eye protection / face protection.
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Chemical characterisation: Mixtures
- Description: Mixture: consisting of the following components.

- Dangerous components:		
CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	25-50%
NLP: 500-033-5	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	
Index number: 603-074-00-8		
Reg.nr.: 01-2119456619-26		

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019

Version number 6

Revision: 01.10.2019

Trade name: **Hydrostop AH+ Concrete Primer Winter (A)**

(Contd. of page 1)

CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40	Bisphenol F epichlorohydrin resin MW <700 Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	25-50%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22	oxirane, mono[(C12-14-alkyloxy)methyl] derivs Skin Irrit. 2, H315; Skin Sens. 1, H317	12.5-25%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- **General information:**

Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Do not leave affected persons unattended.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

- **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eye.

- **After swallowing:**

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters

- **Protective equipment:**

Do not inhale explosion gases or combustion gases.

- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin and eyes

Ensure adequate ventilation

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers).

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

- **Information about fire - and explosion protection:**

No special measures required.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019

Version number 6

Revision: 01.10.2019

Trade name: Hydrostop AH+ Concrete Primer Winter (A)

(Contd. of page 2)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Protect from frost.
Store in dry conditions.
Keep container tightly sealed.
Recommended storage temperature: 5-30 °C
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**

- DNELs		
68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs		
Inhalative	Acute - systemic effects	3.6 mg/m ³ (Worker) (GESTIS DNEL List (June 2018))

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:** When used properly and under normal conditions, breathing protection is not required.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2
Respiratory protection - Gas filters and combination filters according to (DIN EN 141)

- Protection of hands:



Protective gloves

Check protective gloves prior to each use for their proper condition.
Only use chemical-protective gloves with CE-labelling of category III.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves

Recommended materials:
Butyl rubber, BR
Recommended thickness of the material: ≥ 0.5 mm
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.1 mm
Penetration time (min.): < 10

- Eye protection:



Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019

Version number 6

Revision: 01.10.2019

Trade name: **Hydrostop AH+ Concrete Primer Winter (A)**- **Body protection:** protective clothing (EN 13034)

(Contd. of page 3)

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Fluid
 Colour: According to product specification
 - Odour: Aromatic
 - Odour threshold: Not determined.

- pH-value: Not determined.

- Change in condition

Melting point/freezing point: Undetermined.
 Initial boiling point and boiling range: >200 °C

- Flash point: >100 °C

- Flammability (solid, gas): Not applicable.

- Ignition temperature: 300 °C

- Decomposition temperature: Not determined.

- Auto-ignition temperature: Product is not selfigniting.

- Explosive properties: Product does not present an explosion hazard.

- Explosion limits:

Lower: Not determined.
 Upper: Not determined.

- Density at 20 °C: 1.13 g/cm³

- Relative density: Not determined.

- Vapour density: Not determined.

- Evaporation rate: Not determined.

- Solubility in / Miscibility with water: Not miscible or difficult to mix.

- Partition coefficient: n-octanol/water: Not determined.

- Viscosity:

Dynamic at 20 °C: 900 mPas
 Kinematic: Not determined.

- Solvent content:

VOC (EC) 1.08 %

- 9.2 Other information: No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity: No further relevant information available.

- 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions

No dangerous reactions known.

- 10.4 Conditions to avoid

No further relevant information available.

- 10.5 Incompatible materials:

No further relevant information available.

- 10.6 Hazardous decomposition products:

No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects

- Acute toxicity: Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

Oral | LD50 | 11,400 mg/kg (rat)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019

Version number 6

Revision: 01.10.2019

Trade name: **Hydrostop AH+ Concrete Primer Winter (A)**

(Contd. of page 4)

Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LCLo	1 mg/l (rat)
9003-36-5 Bisphenol F epichlorohydrin resin MW <700		
Oral	LD50	23,800 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs		
Oral	LD50	19,200 mg/kg (rat)
Dermal	LD50	>4,500 mg/kg (rabbit)
<ul style="list-style-type: none"> - Primary irritant effect: - Skin corrosion/irritation Causes skin irritation. - Serious eye damage/irritation Causes serious eye irritation. - Respiratory or skin sensitisation May cause an allergic skin reaction. - CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction) - Germ cell mutagenicity Based on available data, the classification criteria are not met. - Carcinogenicity Based on available data, the classification criteria are not met. - Reproductive toxicity Based on available data, the classification criteria are not met. - STOT-single exposure Based on available data, the classification criteria are not met. - STOT-repeated exposure Based on available data, the classification criteria are not met. - Aspiration hazard Based on available data, the classification criteria are not met. 		

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

25068-38-6 reaction product: bisphenol-A-(epichlorohydrin) epoxy resin (number average molecular weight ≤ 700)

IC50	>42.6 mg/l (Bakterien) (18h)
LC50/96 h	1.5 mg/l (fish) (OECD 203 (96 hr))
	1.5 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
EC50 (24)	3.6 mg/l (dpa)
EC50	1.8 mg/l (Daphnia magna) (48h)
EC50	9.4 mg/l (ALGAE) (EPA CFR (72 hr))
	1.7 mg/l (daphnia) (OECD 202 (48 hr))
	11 mg/l (Selenastrum capricornutum) (72h)
NOEC	0.3 mg/l (Daphnia magna) (21d)
MATC	0.55 mg/l (Daphnia magna) (21d)

9003-36-5 Bisphenol F epichlorohydrin resin MW <700

LC50/96 h >100 mg/l (fish)

68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs

EbC50	843 mg/l (Pseudokirchneriella subcapitata)
LC50/96 h	1,800 mg/l (LEPOMUS MACROCHIRUS)
	>5,000 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
NOEC	500 mg/l (Pseudokirchneriella subcapitata) (NOEC (72 hr))

- **12.2 Persistence and degradability** No further relevant information available.- **12.3 Bioaccumulative potential** No further relevant information available.- **12.4 Mobility in soil** No further relevant information available.

- Ecotoxicological effects:

- **Remark:** Toxic for fish

- Additional ecological information:

- General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.- **vPvB:** Not applicable.- **12.6 Other adverse effects** No further relevant information available.

EN

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019

Version number 6

Revision: 01.10.2019

Trade name: **Hydrostop AH+ Concrete Primer Winter (A)**

(Contd. of page 5)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal according to official regulations

- European waste catalogue

08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09
08 02 99	wastes not otherwise specified

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN3082
- **14.2 UN proper shipping name**
- **ADR** 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), Bisphenol F epichlorohydrin resin MW <700)
- **IMDG** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), Bisphenol F epichlorohydrin resin MW <700), MARINE POLLUTANT
- **IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), Bisphenol F epichlorohydrin resin MW <700)

- 14.3 Transport hazard class(es)

- **ADR**
- 
- **Class** 9 (M6) Miscellaneous dangerous substances and articles.
- **Label** 9

- IMDG, IATA

- 
- **Class** 9 Miscellaneous dangerous substances and articles.
- **Label** 9

- **14.4 Packing group**
- **ADR, IMDG, IATA** III

- **14.5 Environmental hazards:** Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
- **Marine pollutant:** Symbol (fish and tree)
- **Special marking (ADR):** Symbol (fish and tree)
- **Special marking (IATA):** Symbol (fish and tree)

- **14.6 Special precautions for user** Warning: Miscellaneous dangerous substances and articles.
- **Danger code (Kemler):** 90
- **EMS Number:** F-A,S-F
- **Stowage Category** A

- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019

Version number 6

Revision: 01.10.2019

Trade name: **Hydrostop AH+ Concrete Primer Winter (A)**

(Contd. of page 6)

- Transport/Additional information:

- ADR	5L
- Limited quantities (LQ)	Code: E1
- Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
- Transport category	3
- Tunnel restriction code	-

- IMDG	5L
- Limited quantities (LQ)	Code: E1
- Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

- UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT \leq 700), BISPHENOL F EPICHLOROHYDRIN RESIN MW <700), 9, III
---------------------------------	---

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU	
- Named dangerous substances - ANNEX I	None of the ingredients is listed.
- Seveso category	E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements	200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements	500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII	Conditions of restriction: 3
- National regulations:	
- Information about limitation of use:	Employment restrictions concerning juveniles must be observed. Employment restrictions concerning pregnant and lactating women must be observed. Employment restrictions concerning women of child-bearing age must be observed.
- 15.2 Chemical safety assessment:	A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
- Abbreviations and acronyms:	ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Sources	Internet: - www.echa.europa.eu - www.baua.de IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance: - www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp - www.dguv.de/ifa/gestis/gestis-dnel-liste

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.10.2019

Version number 6

Revision: 01.10.2019

Trade name: **Hydrostop AH+ Concrete Primer Winter (A)**

- * Data compared to the previous version altered.

(Contd. of page 7)

EN