



ARMOURPREP HEAVY DUTY PVC MEMBRANE CLEANER

PRODUCT INFORMATION

An acetone based solution

Used to achieve a satisfactory hot air weld between Armourplan membranes heavily contaminated by long term exposure to moisture, building site dust and dirt.

Material	Acetone Cleaner
Tin Size	5 Litre
Colour	Clear
Product Number	46030001

ARMOURPREP USE

Wash / scrub the area of membrane where Armourprep solution is to be applied with warm soapy water

Allow to dry

Apply Armourprep to membrane using a clean lint free cloth wearing appropriate PPE in accordance with the MSDS

Allow Armourprep to fully evaporate prior to welding If the membrane becomes wet or soiled after preparation the cleaning regime must be repeated Avoid all contact between Armourprep and polystyrene insulation

Ensure that the cap is firmly placed on the container when not in use.

NOTE – Armourprep will only be supplied with prior agreement from the IKO Polymeric Technical Services Department

FEATURES & BENEFITS

- Effective membrane weld preparation
- Cost effective application



STORAGE

Store in a sealed container in dry conditions at a temperature between 5°C and 25°C. Shelf life 12 months in an unopened container, stored at the above temperature.

TYPICAL PROPERTIES

Characteristic	Armourprep Heavy Duty PVC Membrane Cleaner
properties	PVC Membrane Cleaner
Base	Acetone
Solid Content	0 %
Viscosity	N/A
Colour	Clear
Tack Life	N/A
Coverage Rate	20 m²/litre
Flash Point	-17 °C
Shelf Life	12 months

FURTHER PRODUCT INFORMATION

Full product literature, health & safety and technical sheets are available as downloads from our website www.ikopolymeric.com or on request by email polymeric.marketing@iko.com