

# **Armourplan P**

## 1.2mm Reinforced Single Ply PVC Roofing Membrane

June 2010

#### Introduction

Armourplan P is a 1.2mm thick polyester-reinforced PVC single ply roofing membrane suitable for use in a wide range of roofing applications on both flat and sloping roofs. The membrane can be installed onto most common substrates and is suitable for both new build and refurbishment installations and for specialist applications such as simulated metal roofs. Armourplan P offers enhanced mechanical properties over standard PVC membranes ands is completely UV stable throughout

Armourplan P can be either mechanically fixed using suitable IKOfix fastenings or adhered, and forms a sleek skin on many types of roof application. All overlaps are heat welded using suitable hot-air welding equipment.

### **Features and Benefits**

- Completely UV stable
- Improved tensile strength
- Good mechanical properties and product performance
- Efficient and safe installation
- Secure seam welding quality
- Aesthetically pleasing finish
- Complete range of fixings and accessories available

## **Product Details Roll Dimensions**

	Thickness	Roll Width Options	Length	Colour
Armourplan P	1.2mm	1.06m / 1.50m / 2.12m	20m	Mid Grey or Anthracite

## **Material Composition**

Element	Material		
Material	PVC-P		
Reinforcement	Polyester knitted fabric		

## **Typical Properties**

Property	Test Method	Unit	Result	
Weight	EN 1849-2	g/m²	1576	
Tensile strength	EN 12311-2	N/50mm	MD >1500	
Tonono on ongui			TD >1500	
Elongation at break	EN 12311-2	%	MD >20	
Liongation at break		70	TD >20	
Tear strength	EN 12310-2	N	MD >275	
Tear strength			TD >275	
Dimensional stability 6hrs at 80°C	EN 1107-2	%	MD <0.5	
Dimensional stability 6hrs at 80°C	EN 1107-2	70	TD <0.5	
Low temperature flexibility	EN 495-5:2001	°C	-20	

Notes: MD – Machine Direction TD – Transverse Direction

## **System Components**

To complete the installation of Armourplan P, the system includes a wide range of accessories, including detailing and walkway membrane, cover strips, preformed corners and outlets, standing seam profile, precoated metal sheet for forming edge details, IKOfix fastening systems and termination bars, insulation and vapour control layers, adhesives, cleaners, sealants and rooflights.

### **Other Product Information**

SpectraROOF is part of IKO PLC. Full product literature, health & safety and technical sheets are available as downloads from our website - www.ikogroup.co.uk or on request by email: marketing@ikogroup.co.uk

### **IKO PLC**

#### **Literature Enquiries**

E-Mail: marketing@ikogroup.co.uk Website: www.ikogroup.co.uk

## **Sales Support**

Appley Lane North, Appley Bridge, Wigan, Lancashire WN6 9AB Tel: 0844 873 1063 Fax: 0844 873 1067 E-Mail: sales@ikogroup.co.uk

#### **Technical & Design Services**

Appley Lane North, Appley Bridge, Wigan, Lancashire WN6 9AB Tel: 0844 412 8552 Fax: 0844 412 7229 E-Mail: technical@ikogroup.co.uk



Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.

Company Registered in England No. 2678296 - Registered Office: Appley Lane North, Appley Bridge, Wigan, Lancashire, WN6 9AB