



SUBSTRATE

1. Substrate to minimum of 1:80 achieved falls primed as required for VCL
2. SIG D&T Vapour Control Layer
3. SIG D&T Approved Insulation bonded with IKOPro high performance PU adhesive. Boards to be primed with AH+ WP Primer and all joints to be sealed with AH+ Jointing Tape
4. AH+ Base Coat
5. AH+ Reinforcement Fabric
6. AH+ Top Coat
7. AH+ Jointing Tape
8. SIG D&T protection layer
9. Min. 50mm thick slabs on proprietary supports

Waterproofing should be installed in accordance with BS 6229: (Current Iteration).

AH+ Primer Chart should be consulted for relevant Primer to be utilised before commencing with AH+ waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH+ products and services can be obtained through the contact details printed below.



SIG Design & Technology
 Mannheim House, Gelders Hall Road
 Shepshed, Leicestershire LE12 9NH
 Tel: 0844 443 4778 Fax: 01509 505475
 Internet: www.singleply.co.uk
 Email: info@singleply.co.uk

TITLE:
**AH+ PAVING SLABS ON SUPPORTS
 CONCRETE DECK**

DATE: 02.09.2019	DRAWN BY: RH	SCALE: NTS
---------------------	-----------------	---------------

DRAWING No: AH+18warm	REVISION:
--------------------------	-----------