



1. Structural Metal Deck to minimum 1:80 achieved falls
2. Minimum 18mm Class 3 Plywood or OSB3 primed with AH+ Primer - Consult Primer Chart
3. AH+ Base Coat
4. AH+ Reinforcement Fabric
5. AH+ Top Coat
6. SIG D&T XPS Insulation
7. SIG D&T Water Control Layer
8. Min. 50mm thick slabs on proprietary supports
9. Min. 50mm layer of 20-40mm Rounded Washed Aggregate
10. AH+ Jointing Tape (to be applied to all Timber board joints)

Waterproofing should be installed in accordance with BS 6229: (Current Iteration).

AH+ Primer Chart should be consulted for relevant Primer to be utilised before commencing with AH+ waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH+ products and services can be obtained through the contact details printed below.



SIG Design & Technology
 Mannheim House, Gelders Hall Road
 Shepshed, Leicestershire LE12 9NH
 Tel: 0844 443 4778 Fax: 01509 505475
 Internet: www.singleply.co.uk
 Email: info@singleply.co.uk

TITLE:
**AH+ INVERTED ROOF BUILD-UP
 METAL DECK SECTION**

DATE: 23.08.2019	DRAWN BY: RH	SCALE: NTS
---------------------	-----------------	---------------

DRAWING No: AH+1C inv	REVISION:
--------------------------	-----------