



1. Substrate to minimum 1:80 achieved falls primed with AH+ Primer - Consult Primer Chart
2. AH+ Base Coat
3. AH+ Reinforcement Fabric
4. AH+ Top Coat
5. 100mm overlap of upstand Liquid & Reinforcement to Field area Liquid & Reinforcement
6. Chased Cover Flashing with appropriate sealant
7. 20mm Liquid only to waterproofing termination
8. Brick joints to be Grouted flush with brickwork
9. Brickwork by others

Waterproofing should be installed in accordance with BS 6229: (Current Iteration).

AH+ Primer Chart should be consulted for relevant Primer to be utilised before commencing with AH+ waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH+ products and services can be obtained through the contact details printed below.



SIG Design & Technology
 Mannheim House, Gelders Hall Road
 Shepshed, Leicestershire LE12 9NH
 Tel: 0844 443 4778 Fax: 01509 505475
 Internet: www.singleply.co.uk
 Email: info@singleply.co.uk

TITLE:

AH+ ABUTMENT TO BRICK WALL COLD ROOF

DATE:

23.08.2019

DRAWN BY:

RH

SCALE:

NTS

DRAWING No:

AH+2CR

REVISION: