



1. Substrate to minimum of 1:80 achieved falls primed with AH+ Primer - Consult Primer Chart
2. AH+ Base Coat
3. AH+ Reinforcement Fabric
4. AH+ Top Coat
5. SIG D&T XPS Insulation
6. SIG D&T Water Control Layer
7. SIG D&T drainage layer
8. Sand/Mortar sub-base (Specified & Designed by others)
9. Paviours/Slabs (Specified & Designed by others)
10. 250mm AH+ Liquid & Reinforcement Fabric dressed into outlet
11. SIG D&T Metal Clamp Outlet fully cleaned and free from grease and dirt prior to AH+ application
12. Inspection Chamber for traffickable area - by others

Waterproofing should be installed in accordance with BS 6229: (Current Iteration).

AH+ Primer Chart should be consulted for relevant Primer to be utilised before commencing with AH+ waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH+ products and services can be obtained through the contact details printed below.



SIG Design & Technology  
 Mannheim House, Gelders Hall Road  
 Shepshed, Leicestershire LE12 9NH  
 Tel: 0844 443 4778 Fax: 01509 505475  
 Internet: [www.singleply.co.uk](http://www.singleply.co.uk)  
 Email: [info@singleply.co.uk](mailto:info@singleply.co.uk)

TITLE:  
**AH+ INVERTED ROOF BUILD-UP  
 RAINWATER OUTLET WITH  
 INSPECTION CHAMBER**

DATE: 30.08.2019	DRAWN BY: RH	SCALE: NTS
---------------------	-----------------	---------------

DRAWING No: AH+3 I inv	REVISION:
---------------------------	-----------