



1. Substrate to minimum of 1:80 achieved falls primed with AH+ Primer - Consult Primer Chart
2. AH+ Base Coat
3. AH+ Reinforcement Fabric
4. AH+ Top Coat
5. SIG D&T XPS Insulation
6. SIG D&T Water Control Layer
7. Min. 50mm thick slabs on proprietary supports
8. Min. 50mm layer of 20-40mm Rounded Washed Aggregate
9. AH+ Jointing Tape
10. 250mm AH+ Liquid & Reinforcement Fabric
11. 20mm Liquid only to waterproofing termination
12. Non-Combustible Insulation by others
13. Proprietary Cloaking by others
14. Jubilee Clip or similar compression fitting sealed with appropriate sealant

Waterproofing should be installed in accordance with BS 6229: (Current Iteration).

AH+ Primer Chart should be consulted for relevant Primer to be utilised before commencing with AH+ waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH+ products and services can be obtained through the contact details printed below.



SIG Design & Technology
 Mannheim House, Gelders Hall Road
 Shepshed, Leicestershire LE12 9NH
 Tel: 0844 443 4778 Fax: 01509 505475
 Internet: www.singleply.co.uk
 Email: info@singleply.co.uk

TITLE:

AH+ INVERTED ROOF BUILD-UP HOT METAL PIPE PENETRATION

DATE:

02.09.2019

DRAWN BY:

RH

SCALE:

NTS

DRAWING No:

AH+4B inv

REVISION: