



1. Substrate to minimum of 1:80 achieved falls primed with AH+ Primer - Consult Primer Chart
2. AH+ Base Coat
3. AH+ Reinforcement Fabric
4. AH+ Top Coat
5. SIG D&T XPS Insulation
6. SIG D&T Water Control Layer
7. SIG D&T drainage layer
8. Cast concrete slab (the total loading on insulation to be confirmed by insulation manufacturer as acceptable)

Waterproofing should be installed in accordance with BS 6229: (Current Iteration).

AH+ Primer Chart should be consulted for relevant Primer to be utilised before commencing with AH+ waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH+ products and services can be obtained through the contact details printed below.



SIG Design & Technology
Mannheim House, Gelders Hall Road
Shepshed, Leicestershire LE12 9NH
Tel: 0844 443 4778 Fax: 01509 505475
Internet: www.singleply.co.uk
Email: info@singleply.co.uk

TITLE:
**AH+ INSULATED PODIUM DECK
FLOATING CONCRETE BASE**

DATE: 02.09.2019	DRAWN BY: RH	SCALE: NTS
----------------------------	------------------------	----------------------

DRAWING No: AH+5B inv	REVISION:
---------------------------------	-----------