



1. Substrate to minimum of 1:80 achieved falls primed with AH+ Primer - Consult Primer Chart
2. AH+ Base Coat
3. AH+ Reinforcement Fabric
4. AH+ Top Coat
5. 500mm AH25 Liquid & Reinforcing Membrane
6. AH+ Quartz Sand and transparent sealer
7. SIG D&T drainage layer
8. Concrete Plinth (Specified & Designed by others)
9. Min. 50mm layer of 20-40mm Rounded Washed Aggregate
10. Min. 50mm slabs on proprietary supports
11. SIG D&T Water Control layer
12. SIG D&T XPS Insulation

Waterproofing should be installed in accordance with BS 6229: (Current Iteration).

AH+ Primer Chart should be consulted for relevant Primer to be utilised before commencing with AH+ waterproofing.

The details shown are indicative and for approval only and do not form part of any contract.

Further information on all AH+ products and services can be obtained through the contact details printed below.



SIG Design & Technology
 Mannheim House, Gelders Hall Road
 Shepshed, Leicestershire LE12 9NH
 Tel: 0844 443 4778 Fax: 01509 505475
 Internet: www.singleply.co.uk
 Email: info@singleply.co.uk

TITLE:
**AH+ INVERTED ROOF
 PLINTH ON MEMBRANE**

DATE: 02.09.2019	DRAWN BY: RH	SCALE: NTS
---------------------	-----------------	---------------

DRAWING No: AH+5D inv	REVISION:
--------------------------	-----------