



- ① Structural Deck
- ② SIG D&T Bituminous Vapour Control Layer with Primer
- ③ FDT Adhesive U applied in strips
- ④ SIG D&T Tissue faced Insulation - thickness as specified
- ⑤ Rhenofol CGv PU Adhesive applied in strips
- ⑥ Rhenofol CGv single ply membrane
- ⑦ Hot Air Weld
- ⑧ SIG D&T Termination Bar or Rhenofol laminated metal angle
- ⑨ SIG D&T Full Length Fixing
- ⑩ Rhenofol Contact Adhesive 20
- ⑪ Rhenofol CV single ply membrane
- ⑫ 18mm WBP Plywood or OSB3
- ⑬ Rhenofol PVC Coated Metal

Waterproofing should be installed in accordance with BS 6229:2003 and FDT fixing instructions.

The details shown are indicative and for approval only and do not form part of any contract.

Data sheets for all FDT products are available on request.

Project specifications are available on request.

Further information on all FDT products and services as well as SIG D&T products can be obtained through the contact details printed below.



SIG Design & Technology  
 Mannheim House, Gelders Hall Road  
 Shepshed, Leicestershire LE12 9NH  
 Tel: 0844 443 4778 Fax: 01509 505475  
 Internet: [www.singleply.co.uk](http://www.singleply.co.uk)  
 Email: [info@singleply.co.uk](mailto:info@singleply.co.uk)

TITLE:  
**ADHERED PARAPET DETAIL  
 - UNINSULATED**

|                     |                 |               |
|---------------------|-----------------|---------------|
| DATE:<br>27.08.2015 | DRAWN BY:<br>RH | SCALE:<br>NTS |
|---------------------|-----------------|---------------|

|                        |           |
|------------------------|-----------|
| DRAWING No:<br>CGv-14b | REVISION: |
|------------------------|-----------|