Page 1 of 2

Product Data Sheet May 2014

Coney Green Road, Clay Cross Chesterfield, S45 9HZ

IKO Polymeric

Introduction

Armourplan PVC Standing Seam Profile is a preformed profile used to simulate a metal standing seam joint. The profile is manufactured from PVC and is hot air welded to the installed Armourplan Membrane at a layout specified by the client.

Features & Benefits

- Cost effective standing seam imitation
- Quick and easy installation
- Attractive roof finish

Installation

- 1. Mark out the position of the standing seam profiles across the completed roof area and pull a string/chalk line to achieve a straight edge.
- 2. Tack weld the standing seam profile on to the completed roof to hold into position.
- 3. Option 1 Fully hot air weld each flange of the profile to the roof surface
- 4. Option 2 Tack weld the profile to the roof at 200mm centres along each edge of the profile flange. The tack welds should be staggered.
- 5. Allow a 2mm gap between the end of each profile for expansion / drainage.
- 6. Option At the end of the line of profiles install a small section of Armourplan membrane over the end of the profile by hot air welding to the cut end.

Tel: 01257 488 000 Sales: polymeric.sales.uk@iko.com Technical: polymeric.technical.uk@iko.com








PVC Extrusion

Product Details

Material	PVC
Length	2000mm
Height	30mm
Width	41mm
Colour	Mid Grey / Slate Grey
Product Number	48002000 / 49002000

Technical Specification



Storage

Armourplan Standing Seam Profiles should be kept dry. They should be stored raised off the surface of the roof and covered with a suitable waterproof layer.

Further Product Information

Full product literature, health & safety and technical sheets are available as downloads from our website: www.ikopolymeric.com or on request by email: polymeric.com or on request by email: <a href="htt

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.



Company Registered in England No. 2678296 - Registered Office: Appley Lane North, Appley Bridge, Wigan, Lancashire, WN6 9AB

IKO Polymeric Coney Green Road, Clay Cross Chesterfield, S45 9HZ Tel: 01257 488 000 Sales: polymeric.sales.uk@iko.com Technical: polymeric.technical.uk@iko.com