

ARMOURPLAN PARAPET RAINWATER OUTLETS

PRODUCT INFORMATION

Pre-formed outlets manufactured from PVC and are available in various diameters.

Provide a secure hot air welded solution to roof top drainage when used in conjunction with Armourplan membranes.

Description	PVC Roof Drain
Material	PVC
Colour	Light Grey

FEATURES & BENEFITS

- Good UV resistance and durability
- Excellent mechanical properties and product performance
- Efficient and safe installation
- Secure hot air welded interface



BOX SCUPPER DIMENSIONS

Description	Internal Diameter	90° Angled Base Plate	Spigot Length
PVC 90° Angled Drain 63mm	57mm	H 125mm x Base 150mm x W 345mm	500mm
PVC 90° Angled Drain 75mm	69mm	H 125mm x Base 150mm x W 345mm	500mm
PVC 90° Angled Drain 90mm	84mm	H 125mm x Base 150mm x W 345mm	500mm
PVC 90° Angled Drain 110mm	104mm	H 125mm x Base 150mm x W 345mm	500mm

PVC BOX SCUPPER INSTALLATION

OPTION A

Fix outlet to the substrate using suitable IKOfix fasteners

2 matching flashings of Armourplan D / G membrane should be cut as illustrated

Hot air weld each section of flashing to the outlet flange

Hot air weld the outer edge to the field sheet and upstand membrane



OPTION B

2 matching flashings of Armourplan D / G membrane should be cut as illustrated

Hot Air weld the 2 flashings to the outlet flange remembering to leave the fixing points free from weld

Fix the outlet to the substrate using suitable IKOfix fasteners

Hot air weld the outer edge to the field sheet and upstand membrane.



FURTHER PRODUCT INFORMATION

Full product literature, health & safety and technical sheets are available as downloads from our website

www.ikopolymeric.com or on request by email polymeric.marketing@iko.com.